

RS-TITE®

Outline of RS-TITE®

As you know, the most popular selftapping screw in the world is TAPTITE®. This fame also gathers so many requests for improvement to easy installation, lower installation torque and higher removal torque. **RS-TITE®** has high performance to respond such needs of the marketplace.

Trirobular body :

Low installation torque

The first 3~4 threads from the point is trilobular body. Because trilobular's contact surface is small, installation torque can be lower. TAPTITE®



Special features

- Easy to use when you use by automatic assembly.
- Low and stable installation torque and high maximum stripping torque.
- High removal torque.
- Available for repetitive use.

Why is the removal torque high?

Why is the workability high?

Round body :

High stripping torque

Thread body except of the point is round, of which contact surface is higher. It realizes high stripping torque, high load carrying capability and high removal torque.



Application

***Especially you use by high installation torque and you need repetitive use.
Copying machine, Printer, etc.**

*Trademarks which attached "®" are registered in Japan and/or other countries.

*TAP TITE® is a Registered Trademark Licensed by REMINC.

NITTOSEIKO CO., LTD.

1-6-4, Honjo-nishi,
Higashiosaka City,
Osaka, 578-0965,
Japan

Tel : +81-6-6745-8392

Fax : +81-6-6745-8372

E-mail : sales@nittoseiko.co.jp

URL : <https://global.nittoseiko.com/>